


REMARKS

Applicant encloses a Substitute specification as now amended and a marked-up version showing the changes made to the specification.

The above amendments are being presented to include subheadings, remove multiple dependencies and reference numerals from the claims, and to amend the abstract in order to place the application in better U.S. form.

Should the Examiner have any questions regarding the present application, Applicant respectfully requests that the Examiner contact Applicant's representative at the phone number listed below. While Applicant believes that no fees are due with the submission of this Preliminary Amendment, any fee required may be charged to our Deposit Account No. Deposit Account No. 503342.

Respectfully submitted,

By 
Richard R. Michaud
Registration No. 40,088
Attorney for Applicant

Michaud-Duffy Group LLP
CenterPoint
306 Industrial Park Road
Suite 206
Middletown, CT 06457-1532
Tel: (860) 632-7200
Fax: (860) 632-8269

SAFE WITH SEPARATELY ACCESSIBLE INNER AREASCROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is entitled to the benefit of and incorporates by reference essential subject matter disclosed in International Application No. PCT/DE2003/003061 filed on September 16, 2003 and German Application No. 102 45 917.7 filed on October 1, 2002.

FIELD OF THE INVENTION

[0002] The invention relates to a safe with separately accessible interior areas~~parts of the space inside~~. Such a safe is known from the European Patent Application EP 1 227 448.

BACKGROUND OF THE INVENTION

[0003] Self-service automated teller machines are often set up for depositing and dispensing cash and for accepting checks. For filling and removing cash, strict security regulations apply: there must always be two authorized bank employees in attendance and in many cases armed security personnel must additionally be present. Expenditure on personnel is therefore high. On the other hand, accepted checks are invalidated by an imprint. After that, there is no longer any great security requirement for them.

[0004] In ~~the~~ European Patent Application EP 1 227 448, a safe is disclosed with entry points for checks and cash in the upper part of the safe and with collection boxes in the lower part of the safe is proposed. In that,~~in which~~ safe the lower part with the collection boxes is closed by a solid inner safe door, which has no cutouts, and the upper

part is closed by an additional outer safe door, which also covers the inner safe door.

[0005] The object of the invention is to propose a safe which has differently secured inner areas.

~~The object is achieved by the features of claim 1.~~

SUMMARY OF THE INVENTION

[0006] According to aspects of the present invention, ~~the a~~ safe is provided with an inner safe door and an outer safe door, which at least partially overlap with each other, ~~it being.~~ It is possible for the safe doors to pivot about the same pivoting axis between a position covering the opening of the safe and a position releasing said opening, and. In the preferred embodiment of the present invention, the inner safe door ~~having~~ has a cutout through which at least one part of the space inside is accessible after the outer safe door is opened, while the remaining inner area is accessible only after both safe doors are opened.

[0007] ~~This has the~~An advantage of allowing the use of ~~the~~ the present invention is that a standardized safe, the can be retrofitted. The space inside the safe which can be provided with internal fittings as desired. All that is necessary is to design the inner safe door in a way corresponding to the internal fittings.

[0008] The overlapping arrangement of the safe doors makes it possible according to a preferred ~~refinement~~ embodiment of the present invention to assign each safe door a dedicated locking mechanism which can be actuated by a lock.

~~[0009] In this case, according to a development~~Preferably, the safe door locking mechanisms can be actuated by a single lock, different unlocking privileges being assigned to different keys in such a way that a key with a low privilege is only able to unlock the outer safe door, while both safe doors can be unlocked at the same time with a key of high privilege.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] An exemplary embodiment of the invention is explained below on the basis of the accompanying drawing, in which:

[0011] Figure 1 shows an automated teller machine in a plan view taken in section along the line ~~I-I~~I1-1 in Figure 3;

[0012] Figure 2 shows a front view of the automated teller machine represented in Figure 1, with the safe doors opened; and

[0013] Figure 3 shows a front view of the automated teller machine represented in Figure 1 with the outer safe door opened and the inner safe door closed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0014] In Figure 1, an automated teller machine 10 is represented in a sectioned plan view. The automated teller machine 10 comprises a safe 12 and a top attachment 14 with an operator control panel 16 (not represented in any more detail). Of the operating elements that are customary in the case of automated teller machines, only a depositing/dispensing compartment 18 for checks and banknotes is represented.

[0015] The side walls 20 of the safe 12 are armored, as are its base plate 22 and top plate 24. A likewise armored outer safe door 26 and an inner safe door 28 are articulated on one of the side walls 20a and can be pivoted individually about a pivoting axis 30 shared by both, between a position covering the opening 32 of the safe and a position releasing said opening. The outer safe door 26 is provided with a safe lock 34, which in its closed position connects the two safe doors 26, 28 to each other and locks them to the safe 12, in a first opening position unlocks only the outer safe door 26 and in a second opening position keeps the inner safe door 28 closed together with the outer safe door 26 but unlocked from the safe, so that the joined-together assembly of the two safe doors 26, 28 can be opened like a single safe door.

[0016] Fitted in the interior space of the safe 12 are a check container 36 and a banknote store 38. The latter contains four banknote boxes 38a - 38d. A conveying path 40 connects the depositing/dispensing compartment 18 to the check container 36 and the banknote boxes 38a - 38d. The inner safe door 28 has a cutout 42, which leaves the check container 36 clear, but covers over the banknote store 38 and the conveying path 40. When the inner safe door 28 is closed, access is therefore only possible to the check container 36, to which, as mentioned above, a low security level applies. While four banknote boxes have been shown and described, the present invention is not limited in this regard as any number of banknote boxes can be employed without departing from the broader aspects of the invention.

[0017] If a banknote box 38a - 38d is to be exchanged, emptied or filled, or else the conveying path 40 is to be accessed, the safe lock 34 has to be actuated with a key of high

privilege. By means of this key, the outer safe door 26 and the inner safe door 28 are locked together, but can be jointly unlocked from the safe. They can then be opened like a single safe door. In this case, the security measures described above are to be observed. On the other hand, the emptying of the check container 36 can be performed by a single person without infringing any security regulations. The saving on personnel expenditure is therefore considerable.

[0018] The invention makes it possible to arrange internal fittings of low and high security relevance at any desired locations of the space inside the safe. Internal fittings with low security relevance also do not have to be grouped together, but instead it is possible for the inner safe door 28 to be provided with a number of cutouts that are shaped and arranged as desired.

[0019] It is also possible to provide the safe 12 with more than two security levels: all that is then necessary is to adapt the number of inner safe doors to the number of security levels and to provide the safe lock 34 with a corresponding number of locking positions. The safe lock 34 may be able to be actuated with a mechanical key or be designed as a code lock which can be actuated electrically. It is also conceivable to provide the inner safe door, or a number of them, with separate locks.

[0020] While preferred embodiments of the present invention have been shown and described, the present invention is not limited in this regard as those skilled in the pertinent art to which the present invention pertains will understand that

various modifications can be made without departing from the
scope of the present invention.